



**DANGER!**

H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H410 Very toxic to aquatic life with long lasting effects.

**Prevention:**

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.  
P235 Keep cool.  
P240 Ground / bond container and receiving equipment.  
P241 Use explosion-proof electrical / ventilating / light / equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust / fume / gas / mist / vapors / spray.  
P264 Wash thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves / eye protection / face protection.

**Response:**

P302+352 IF ON SKIN: Wash with plenty of soap and water.  
P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.  
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
P310 Immediately call a POISON CENTER or doctor / physician.  
P313 Get medical advice / attention.  
P321 Specific treatment (see information on this label).  
P333+313 If skin irritation or a rash occurs: Get medical advice / attention.  
P362 Take off contaminated clothing and wash before reuse.  
P363 Wash contaminated clothing before reuse.  
P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.  
P391 Collect spillage.

**Storage:**

P403+233 Store in a well ventilated place. Keep container tightly closed.

**Disposal:**

P501 Dispose of contents / container in accordance with local / national regulations.



(509)452-4476 (800)579-6832  
2809 FRUITVALE BLVD.  
YAKIMA, WASHINGTON, USA 98902

**CleanUP**

# DeStick®

**BREAKS DOWN STICKER ADHESIVES INADVERTENTLY APPLIED TO FRUIT HANDLING EQUIPMENT.  
DISEÑADO PARA DESPRENDER ADHESIVOS EN MAQUINARIA PARA LA INDUSTRIA FRUTICOLA.**

**DIRECTIONS:** FOR BEST RESULTS DeStick SHOULD BE USED "AS IS" UNDILUTED. DeStick CAN BE APPLIED BY WIPING, BRUSHING OR SPRAYING. DeStick IS NOT COMPATIBLE WITH MOST GENERAL PURPOSE PLASTIC SPRAYERS. USE FLUORINATED PLASTICS OR METAL CONTAINERS OR THOROUGHLY RINSE APPLICATION EQUIPMENT WITH CLEAR WATER AFTER EACH USE TO ENHANCE LONGEVITY. CARE SHOULD BE TAKEN NOT TO APPLY DeStick TO INCOMPATIBLE SURFACES SUCH AS PLASTIC OR RUBBER. ALWAYS TEST A SMALL AREA BEFORE PROCEEDING. USING MINIMAL APPLICATION TIME, SIMPLY RINSE PRODUCT OFF WITH CLEAR WATER.

**Aplicación:** Para lograr el mejor resultado, aplicar "DeStick" sin diluir. "DeStick" puede aplicarse directamente con un paño, brocha o atomizador. "DeStick" por lo general no es compatible con la mayoría de los aplicadores plásticos. De preferencia utilice contenedores plásticos fluorizados o contenedores metálicos. Enjuague cada vez y muy bien todo equipo utilizado en la aplicación de este producto para minimizar desgaste. Ponga especial atención de modo de no aplicar "DeStick" en superficies incompatibles tales como plástico o gomas. Realice pequeños ensayos antes de proceder. Dejar reposar por algunos minutos, luego enjuague con agua limpia para eliminar residuos del producto.

**STORAGE:** DeStick IS SHIPPED IN STEEL CONTAINERS AND SHOULD REMAIN CLOSED IN ITS ORIGINAL PACKAGING UNTIL USE. DO NOT ALLOW THIS PRODUCT TO FREEZE. STORE INSIDE AT TEMPERATURES BETWEEN 40°-100° F. (4.4°C - 37.7°C) WITH CAPS SECURED WHEN NOT IN USE. CAUTION! DO NOT CUT OR WELD EMPTY CONTAINER AS VAPORS MAY IGNITE.

**Almacenado:** Este producto es transportado en contenedores metálicos y debe ser mantenido en su embase original y cerrado hasta que sea utilizado totalmente. No dejar que este producto llegue a punto de congelación. Almacenar bajo techo a temperaturas entre 4° - 37° C (40° - 100° F). Mantener este producto con tapa rosca debidamente apretada cuando no este en uso. ¡PELIGRO! NO REALICE CORTES NI SOLDADURA EN TAMBORES QUE CONTENGAN RESIDUOS DE ESTE PRODUCTO PUES LOS GASES EMITIDOS POR ESTA SUBSTANCIA SON INFLAMABLES.

**NON-WARRANTY:**SINCE ACTUAL USE BY OTHERS IS BEYOND OUR CONTROL, NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY U.S. SYNTEC CORPORATION, NOR DOES U.S. SYNTEC CORPORATION ASSUME ANY LIABILITY ARISING OUT OF THE USE BY OTHERS OF THE PRODUCT REFERRED HEREIN.

**CONDICIONES DE LA GARANTIA:** DEBIDO A QUE EL USO DE ESTE PRODUCTO POR TERCEROS ESTÁ FUERA DE NUESTRO CONTROL, U. S. SYNTEC CORPORATION NO EXTENDERÁ GARANTÍA ALGUNA, COMO TAMPOCO U.S. SYNTEC CORPORATION SE HARÁ RESPONSABLE POR EL USO DE ESTE PRODUCTO POR TERCEROS.



**ERG 154**



**CONTAINER MUST BE EMPTIED, RINSED AND CAPPED BEFORE RETURNING TO U.S. SYNTEC CORP**

LOT# 11 CUDS55 MD2366

55 GALLONS (208.23 LITERS) NET WT. 385 LBS.