



DANGER!

H303 May be harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.

Prevention:

P260 Do not breathe mist / vapors / spray.
P264 Wash thoroughly after handling.
P280 Wear protective gloves / eye protection / face protection.

Response:

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
P310 Immediately call a POISON CENTER or doctor / physician.
P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents / container in accordance with local / national regulations.



(509)452-4476 (800)579-6832
2809 FRUITVALE BLVD.
YAKIMA, WASHINGTON, USA 98902

CleanUP

DeterAL HIGH FOAM HF

**HIGH ALKALINITY, HIGH FOAM, HEAVY DUTY DETERGENT CLEANER
FOR USE IN FISH, POULTRY, MEAT AND BEVERAGE PROCESSING FACILITIES
CLEANSE EQUIPMENT, FLOORS & WALLS, TILE, CONCRETE, etc.**

DIRECTIONS: FOR ROUTINE CLEANING DeterAL HF SHOULD FIRST BE DILUTED TO A RATIO OF 2 oz per 1 GALLON OF WATER. HEAVIER BUILDUP 6 oz per 1 GALLON WATER WITH EXTREME BUILDUP AT 14 oz per 1 GALLON WATER. WHEN USING THE CAUSTIC TITRATION KIT #USSTK3000-Z, THE EFFECTIVE ALKALINITY RANGE IS 0.2, .5 AND 10.0% RESPECTIVELY. CONCENTRATIONS AND METHODS OF APPLICATION VARY DEPENDING ON DEGREE OF BUILDUP TO BE REMOVED AND SURFACE COMPATIBILITY. WATER TEMPERATURE SHOULD BE ABOVE 70° F, PREFERABLY 115° F FOR THE BEST BREAKDOWN OF PROTEINS AND SOILS. ALLOW 10-15 MINUTES TO PENETRATE. FOLLOW WITH A HOT WATER RINSE BEFORE PRODUCT DRIES.

APLICACIÓN:

STORAGE: DeterAL HF SHOULD REMAIN CLOSED IN ITS ORIGINAL PACKAGING UNTIL USE. DO NOT ALLOW THIS PRODUCT TO FREEZE. STORE INSIDE AT TEMPERATURES BETWEEN 40°-100° F.(4.4°C - 37.7°C) WITH CAPS SECURED WHEN NOT IN USE.

ALMACENAMIENTO: DeterAL HF ACERO DEJÁNDOLO EN SU ENVASE ORIGINAL PERMANENTEMENTE HASTA SU UTILIZACIÓN. NO PERMITA QUE ESTE PRODUCTO LLEGA A PUNTO DE CONGELACION. ALMACENAR BAJO TECHO A TEMPERATURAS ENTRE 4° Y 38° C (40° - 100° F) MANTENIÉNDOLO SELLADO CON SUS TAPAS ROSCA DEBIDAMENTE INSTALADAS MIENTRAS NO SE UTILICE.

NON-WARRANTY:SINCE ACTUAL USE BY OTHERS IS BEYOND OUR CONTROL, NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY U.S. SYNTEC CORPORATION, NOR DOES U.S. SYNTEC CORPORATION ASSUME ANY LIABILITY ARISING OUT OF THE USE BY OTHERS OF THE PRODUCT REFERRED HEREIN.

CONDICIONES DE LA GARANTIA: DEBIDO A QUE EL USO DE ESTE PRODUCTO POR TERCEROS ESTÁ FUERA DE NUESTRO CONTROL, U. S. SYNTEC CORPORATION NO EXTENDERÁ GARANTÍA ALGUNA, COMO TAMPOCO U.S. SYNTEC CORPORATION SE HARÁ RESPONSABLE POR EL USO DE ESTE PRODUCTO POR TERCEROS.



ERG 154



**CONTAINER MUST BE EMPTIED, RINSED AND CAPPED
BEFORE RETURNING TO U.S. SYNTEC CORP**

LOT#11 CUDAL HF 55 MD2 8 3 8

55 GALLONS (208.19 LITERS) NET WT. 520 LBS.

REV. 05/17