



DANGER!

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Prevention:

P260 Do not breathe mist / vapors / spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

Response:

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents / container in accordance with local / national regulations.

CleanUP

HydroFoam AC

A CONCENTRATED FOAMING ACID CLEANER SOLUTION FOR STAINLESS STEEL PLASTIC, WOOD, GLASS AND GENERAL PLANT AND EQUIPMENT CLEANING

DIRECTIONS: HydroFoam AC SHOULD BE APPLIED AS IS OR DILUTED 16:1 (1 part HydroFoam AC to 16 parts water) WITH WATER ABOVE 70° F. USE OF AN ELECTRONIC PH METER OR PH PAPER IS RECOMMENDED TO MAINTAIN A DILUTION WITH AN APPROXIMATE PH LEVEL OF 2 FOR OPTIMAL PERFORMANCE. A FRESH WATER RINSE IS RECOMMENDED AFTER TREATMENT WITH THIS PRODUCT. FOR BEST RESULTS PERFORM A PRE-CLEAN WITH AN APPROPRIATE *CLEAN UP DeterAL PRODUCT*. SANITATION FOAMER SYSTEM APPLICATIONS SHOULD USE THE GREY (.128) METERING TIP.

STORAGE: DO NOT ALLOW THIS PRODUCT TO FREEZE. STORE INSIDE AT TEMPERATURES BETWEEN 40°-100° F. (4.4°C - 37.7°C) WITH CAPS SECURED WHEN NOT IN USE. PRODUCT IS HEAVY AND IF DOUBLE STACKED COULD COLLAPSE BOTTOM PALLETS AND/OR DRUMS CAUSING THEM TO TOPPLE AND CAUSE AN ACCIDENT.

ALMACENAMIENTO: EVITAR QUE ESTE PRODUCTO SE CONGELE. MANTENER ALMACENADO EN TEMPERATURAS ENTRE 40 ° -100 ° F (4,4 ° C - 37,7 ° C) CON TAPAS DEBIDAMENTE COLOCADAS EN LOS TAMBORES CUANDO NO ESTE EN USO. ESTE PRODUCTO ES EXTEMADAMENTE PESADO. NO APILAR SOBRE OTRO TAMBOR. EXISTE LA POSIBILIDAD DE COLAPSAR Y CAERSE LO QUE PUEDE PROVOCAR UN ACCIDENTE.

NON-WARRANTY: SINCE ACTUAL USE BY OTHERS IS BEYOND OUR CONTROL, NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY U.S. SYNTEC CORPORATION, NOR DOES U.S. SYNTEC CORPORATION ASSUME ANY LIABILITY ARISING OUT OF THE USE BY OTHERS OF THE PRODUCT REFERRED HEREIN.

CONDICIONES DE LA GARANTIA: EN CONSECUENCIA QUE EL USO DE ESTE PRODUCTO POR TERCEROS ESTÁ FUERA DE NUESTRO CONTROL, U. S. SYNTEC CORPORATION NO EXTENDERÁ GARANTÍA ALGUNA, COMO TAMPOCO U.S. SYNTEC CORPORATION SE HARÁ RESPONSABLE POR EL USO DE ESTE PRODUCTO POR TERCEROS.

ERG 154



CONTAINER MUST BE EMPTIED, RINSED AND CAPPED BEFORE RETURNING TO U.S. SYNTEC CORP

LOT# 11 CUHFAC55 MB3655

55 GALLONS (208.19 LITERS) NET WT. 550 LBS.



(509)452-4476 (800)579-6832
2809 FRUITVALE BLVD.
YAKIMA, WASHINGTON, USA 98902

