



**DANGER!**

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

**Prevention:**

P260 Do not breathe mist / vapors / spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

**Response:**

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents / container in accordance with local / national regulations.

# PHASE 1

# Neutral Tank



## A CONCENTRATED SOLUTION FOR USE AS A NEUTRALIZER OF ACID BASE DUMP TANK ADDITIVES BEFORE DISCHARGING

**SUGGESTED APPLICATION:** THE AMOUNT OF PHASE 1 NEUTRAL TANK PH-UP REQUIRED FOR NEUTRALIZATION IS DEPENDANT ON THE VOLUME AND PH LEVEL OF THE DUMP TANK. EXAMPLE, IF THE PH LEVEL OF THE DUMP TANK IS BELOW A PH OF 3, USER IS ADVISED TO BEGIN WITH SMALL AMOUNTS, APPROXIMATE (1-2 GALLONS) AT FIRST, TO BETTER DETERMINE PROPORTIONS TO BE USED. RECHECK PH OF DUMP TANK AFTER A FEW MINUTES OF GOOD CIRCULATION. IF PH LEVEL REMAINS BELOW A PH OF 7, CONTINUE ADDING NEUTRAL TANK 1 IN INCREASINGLY SMALLER AMOUNTS UNTIL THE DESIRED DUMP TANK PH LEVEL IS ACHIEVED.

**APLICACIÓN RECOMENDADA:** LA CANTIDAD DE PHASE 1 NEUTRAL REQUERIDA PARA LA NEUTRALIZACIÓN DEPENDE DEL VOLUMEN QUÍMICO DE CUALQUIERA SEA LAS SUBSTANCIAS Y NIVELES DE PH EN EL ESTANQUE DE VERTIDO. POR EJEMPLO, SI EL NIVEL DE PH DEL ESTANQUE DE VERTIDO ES MENOR QUE 3, SE RECOMIENDA APLICAR PEQUEÑAS CANTIDADES, APROXIMADAMENTE (1 A 2 GALONES) EN UN PRINCIPIO, PARA DETERMINAR QUE PROPORCIONES ES NECESARIO USAR, VUELVA A REVISAR EL PH DEL ESTANQUE DE VERTIDO AL CABO DE ALGUNOS MINUTOS DE TENER BUENA CIRCULACIÓN DE AGUA. SI LOS NIVELES DE PH SE MANTIENEN BAJO 7, CONTINÚE APLICANDO NEUTRAL TANK 1 EN PROPORCIONES MÁS PEQUEÑAS CADA VEZ HASTA QUE LLEGUE AL PH QUE NECESITA.

**STORAGE:** DO NOT ALLOW THIS PRODUCT TO FREEZE. STORE INSIDE AT TEMPERATURES BETWEEN 40°-100° F. (4.4°C - 37.7°C) WITH CAPS SECURED WHEN NOT IN USE. PRODUCT IS HEAVY AND IF DOUBLE STACKED COULD COLLAPSE BOTTOM PALLETS AND/OR DRUMS CAUSING THEM TO TOPPLE AND CAUSE AN ACCIDENT.

**ALMACENAMIENTO:** NO PERMITA QUE ESTE PRODUCTO SE CONGELE. ALMACENAR EN ÁREAS CERRADAS Y CUBIERTAS CUYA TEMPERATURA SE ENCUENTRE ENTRE 40° - 100° F (4° - 37° C) CON LAS TAPAS BIEN CERRADAS SI NO ESTA USANDO EL PRODUCTO. ESTE PRODUCTO ES EXTRAORDINARIAMENTE PESADO. SI ES APILADO DOBLE, ES POSIBLE QUE COLAPSE EL TAMBOR CONJUNTAMENTE CON EL PALET LO QUE PUEDE PROVOCAR UN ACCIDENTE.

**NON-WARRANTY:** SINCE ACTUAL USE BY OTHERS IS BEYOND OUR CONTROL, NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY U.S. SYNTEC CORPORATION, NOR DOES U.S. SYNTEC CORPORATION ASSUME ANY LIABILITY ARISING OUT OF THE USE BY OTHERS OF THE PRODUCT REFERRED HEREIN.

**CONDICIONES DE LA GARANTIA:** EN CONSECUENCIA QUE EL USO DE ESTE PRODUCTO POR TERCEROS ESTÁ FUERA DE NUESTRO CONTROL, U. S. SYNTEC CORPORATION NO EXTENDERÁ GARANTÍA ALGUNA, COMO TAMPOCO U.S. SYNTEC CORPORATION SE HARÁ RESPONSABLE POR EL USO DE ESTE PRODUCTO POR TERCEROS.



 (509)452-4476 (800)579-6832  
2809 FRUITVALE BLVD.  
YAKIMA, WASHINGTON, USA 98902

ERG 154



**CONTAINER MUST BE EMPTIED, RINSED AND CAPPED BEFORE RETURNING TO U.S. SYNTEC CORP**

LOT# 11 P1 NTPHUP55 MD2648

55 GALLONS (208.19 LITERS) NET WT. 587 LBS.

REV. 10/15