



**DANGER!**

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

**Prevention:**

P260 Do not breathe mist / vapors / spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

**Response:**

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents / container in accordance with local / national regulations.



(509)452-4476 (800)579-6832  
2809 FRUITVALE BLVD.  
YAKIMA, WASHINGTON, USA 98902

## PHASE 2

# Alkal<sup>®</sup>

**CONCENTRATED DETERGENT CLEANER FOR USE IN THE BRUSH SECTION TO AID IN THE REMOVAL OF NATURAL WAX, MOLD, MILDEW AND SOIL DEPOSITS ON APPLES**  
**DETERGENTE INDUSTRIAL PARA SECCION DE CEPILLOS Y PARA AYUDAR A LA EXTRACCION DE CERA NATURAL, MOHO, HONGOS Y DEPOSITOS MINERALES EN MANZANAS.**

**SUGGESTED APPLICATION: SPRAY BAR METHOD:** PHASE-2 ALKAL PG SHOULD BE METERED AT A RATE SUFFICIENT TO ACHIEVE DESIRED AMOUNT OF FOAM AND PH LEVELS OF 10 TO 12. **DRIP SYSTEM METHOD:** PHASE-2 ALKAL PG SHOULD FIRST BE DILUTED TO A RATIO OF 1 GALLON CLEANER PER 30 GALLONS WATER THEN ADJUSTED TO A RATE SUFFICIENT TO ACHIEVE DESIRED FOAM AND PERFORMANCE LEVELS. CONCENTRATIONS MAY BE VARIED IN BOTH METHODS DEPENDING ON PROCESS SPEED AND CONDITION OF FRUIT. FOR BEST RESULTS WATER TEMPERATURE SHOULD BE ABOVE 70° F. FOLLOWED WITH A WARM WATER RINSE.

**APLICACION:** POR METODO DE BARRA: APLICAR PHASE-2 ALKAL PG EN FORMA CONTROLADA EN UNA PROPORCION SUFICIENTE Y CONTROLADA DE MODO DE LOGRAR LA ESPUMA DESEADA Y NIVEL DE PH DE 10 A 12. **METODO POR GOTEO:** DELUIR PHASE-2 ALKAL PG EN RAZON DE 1 GALON POR CADA 30 GALONES DE AGUA Y LUEGO IR AJUSTANDO HASTA LOGRAR LA ESPUMA DESEADA Y NIVELES DE RENDIMIENTO. LAS CONCENTRACIONES VARIARAN PARA CADA METODO Y DEPENDERA DE LA VELOCIDAD DE PROCESO Y CONDICIONES DE LA FRUTA. PARA LOGRAR MEJORES RESULTADOS, LA TEMPERATURA DEL AGUA DEBERIA ESTAR A LO MENOS 70 GRADOS FARENHIEIT, SEGUIDO DE ENJUAGUE EN AGUA TIBIA.

**STORAGE: DO NOT ALLOW THIS PRODUCT TO FREEZE.** STORE INSIDE AT TEMPERATURES BETWEEN 40°-100° F.

**ALMACENAMIENTO:** NO EXPONER ESTE PRODUCTO A PUNTO DE CONGELACION. ALMACENAR A TEMPERATURAS ENTRE 4.4 C a 37.7 C (40 A 100 F).

**NON-WARRANTY:**SINCE ACTUAL USE BY OTHERS IS BEYOND OUR CONTROL, NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY U.S. SYNTEC CORPORATION, NOR DOES U.S. SYNTEC CORPORATION ASSUME ANY LIABILITY ARISING OUT OF THE USE BY OTHERS OF THE PRODUCT REFERRED HEREIN.

**NO GARANTÍA:** DESDE EL ACTUAL USO POR OTROS FUERA DE NUESTRO CONTROL, NINGUNA GARANTÍA, EXPRESA O IMPLÍCITA, ES HECHA POR U.S. SYNTEC CORPORATION, TAMPOCO U.S. SYNTEC CORPORATION ASUME NINGUNA RESPONSABILIDAD QUE SURJA DE LOS OTROS POR EL USO DE ESTE DOCUMENTO A QUE SE REFIERE EL PRODUCTO.



ERG 154



**CONTAINER MUST BE EMPTIED, RINSED AND CAPPED BEFORE RETURNING TO U.S. SYNTEC CORP**

LOT# 11 P2 AL PG5 5 MD2 9 5 8

55 GALLONS (208.19 LITERS) NET WT. 508 LBS.

REV. 09/15