



DANGER!

Phase 3

SHELLAC

PHASE 3 SHELLAC IS A HIGH GLOSS COATING FOR USE AS A POST HARVEST APPLE COATING FOR DOMESTIC MARKETS

H226 Flammable liquid and vapor.
H336 May cause drowsiness and dizziness.

Prevention:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

Response:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

Storage:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents / container in accordance with local / national regulations.

SUGGESTED APPLICATION: APPLY PHASE 3 SHELLAC UNDILUTED USING NO MORE THAN NECESSARY FOR A HIGH GLOSS COATING. APPLY TO THOROUGHLY CLEANED, RINSED AND DRIED FRUIT USING ACCEPTABLE INDUSTRY METHODS. APPLICATION BRUSHES AND EQUIPMENT SHOULD BE CLEANED REGULARLY. USE OF ADDITIONAL ANTI-FOAM SHOULD BE USED SPARINGLY AND ONLY IF NEEDED.
SOLICITUD DE PROPUESTAS: Aplicación FASE 3 Shellac puro sin usar más de lo necesario para un alto el GLOSS RECUBRIMIENTO. Aplicará a limpiar, enjuagarlos y frutos secos USO ACEPTABLE INDUSTRIA MÉTODOS. SOLICITUD CEPILLOS Y EQUIPO debe limpiarse regularmente. USO DE LUCHA CONTRA LA ESPUMA ADICIONAL deben utilizarse con moderación y sólo si es necesario.

INGREDIENTS: WATER, FOOD GRADE SHELLAC, ISOPROPYL ALCOHOL, VEGETABLE FATTY ACID SOAP, SILICONE ANTI-FOAM.
INGREDIENTES: AGUA, COMIDA DE GRADOS laca, alcohol isopropílico, vegetales de ácidos grasos SOAP, SILICONA ANTI ESPUMA.

STORAGE: DO NOT ALLOW THIS PRODUCT TO FREEZE. STORE INDOORS AT TEMPERATURES BETWEEN 40°-100° F. (4.4°C - 37.7°C) WITH CAPS SECURED WHEN NOT IN USE. THIS PRODUCT IS **FLAMMABLE**. STORE AWAY FROM ALL SOURCES OF IGNITION. SHELF LIFE OF THIS PRODUCT DEPENDS GREATLY ON THE CONDITIONS UNDER WHICH IT IS STORED. PRODUCT SHOULD BE USED WITHIN THIRTY DAYS UPON HAVING BEEN OPENED.

ALMACENAMIENTO: NO PERMITEN ESTE PRODUCTO A CONGELAR. CONSERVACIÓN DE INTERIORES a temperaturas entre 40 ° - 100 ° F (4,4 ° C - 37,7 ° C) SEGURIDAD CON MAYÚSCULAS cuando no esté en uso. ESTE PRODUCTO ES INFLAMABLE, TIENDA lejos de todas las fuentes de ignición. PLATAFORMA LA VIDA DE ESTE PRODUCTO, depende en gran medida de las condiciones en las que se almacena.

CAUTION TO USER: AS WITH ALL SHELLAC COATINGS, THE PRESENCE OF MOISTURE OR CONDENSATION ON THE DRIED PRODUCT CAN CAUSE SOME WHITING TO THE COATING. ALTHOUGH PHASE 3 SHELLAC HAS A HIGH THRESHOLD TO WHITING, VARYING CONDITIONS THAT MAY LEAD TO WHITING ARE BEYOND THE CONTROL OF U.S. SYNTEC CORPORATION.

ATENCIÓN AL USUARIO: Como con todos los Shellac RECUBRIMIENTOS, presencia de humedad o condensación en el producto seco puede causar algunos merlán del recubrimiento. AUNQUE FASE 3 Shellac tiene un alto umbral para el merlán, las diferentes condiciones que pueden dar lugar a merlán escapan al control de EE.UU. SYNTEC CORPORATION.

NON-WARRANTY: SINCE ACTUAL USE BY OTHERS IS BEYOND OUR CONTROL, NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY U.S. SYNTEC CORPORATION, NOR DOES U.S. SYNTEC CORPORATION ASSUME ANY LIABILITY ARISING OUT OF THE USE BY OTHERS OF THE PRODUCT REFERRED HEREIN.

CONDICIONES DE LA GARANTIA: DEBIDO A QUE EL USO DE ESTE PRODUCTO POR TERCEROS ESTÁ FUERA DE NUESTRO CONTROL, U. S. SYNTEC CORPORATION NO EXTENDERÁ GARANTÍA ALGUNA, COMO TAMPOCO U.S. SYNTEC CORPORATION SE HARÁ RESPONSABLE POR EL USO DE ESTE PRODUCTO POR TERCEROS.

ERG 127



CONTAINER MUST BE EMPTIED, RINSED AND CAPPED BEFORE RETURNING TO U.S. SYNTEC CORP

LOT# 11 P3 S55 MD2 328

55 GALLONS (208.19 LITERS) NET WT. 456 LBS.

